

T1025 (T255)

Sub-Compact, Series 1
26 hp maximum

11.495€*

*excl. BTW & frontlader




TYM
ZUID-KOREA

CNUDD E
BV



A sub-compact tractor engineered for productivity inside and out

The T1025 tractor is proof that great things can indeed come in small packages. Offering enhanced power without sacrificing maneuverability, it's equipped with a powerful engine and ergonomic operator controls, ensuring both performance and comfort.



1. PTO lever for mid and rear rpm



3. Foldable ROPS




5. Independent electro-hydraulic PTO switch



2. 2-range hydrostatic transmission (HST)



4. Throttle lever



6. Dial adjustment for mower height



Ergonomic features for enhanced productivity

A wide operator cabin with a flat floor offers good visibility and ample leg room, promoting comfortable operation. All controls are within arm's reach, including a dial to control the cutting height of the mid-mount implement. The accelerator, brake pedal, differential lock, and parking brake are easily accessible on the floor of the cabin, located precisely where you expect them to be. These features make this tractor easy to operate, even for novice drivers.



High torque, water-cooled Yanmar diesel engine

The Japanese made Yanmar engine offers more torque with less revs compared to competitors in its class. Since it is water cooled, the engine warms up faster and stabilized temperature more effectively while the tractor is running. The engine is also Stage V certified, including for noise emission standards.



2-range HST for smooth operation

Accompanied by the power steering, the responsive 2-range hydrostatic controls on this tractor ensures a smooth ride. It reduces the need for operator effort, particularly while operating the optional front-end and rear implements.



3-point hitch with powerful lift capacity

The 3-point linkage on the rear has an impressive lift capacity that reaches the end ball joint. The rear PTO control can be used to adjust rpm based on the task, increasing it for more intensive ground engagement like slashing or digging.



Controls to speed up, slow down, raise or lower implements

Even while the tractor is in motion, a dedicated PTO lever can be used to speed up or slow down implement rpm, while the dial can raise and lower implements at the prescribed speed.



Foldable ROPS for storage in low-ceiling structures

The Roll Over Protective Structure (ROPS) of the tractor is designed to be folded, allowing for easy storage in low-ceiling garages or sheds.

Technical specifications T1025 (T255)

ENGINE	
Engine manufacturer	Yanmar 3TNV76-UD
Type	Natural aspiration
engine power nominal	18.9 kW
engine power maximum	26 hp
Rated engine speed	2800 rpm
No. of cylinders	3
Displacement	1116 cc
Air cleaner	Single dry
Alternator	12V, 40A
Fuel system	IDI
POWERTRAIN	
Transmission type	HST
No. of speeds	HST: 2-Range
Max. traveling speed	HST: 20 km/h
Brakes	Wet disc
Steering	Hydrostatic
Clutch	Dry single plate
CAPACITIES	
Fuel tank	22 L
Coolant	3.6 L
Crankcase	2.7 L
Transmission/Hydraulics system	14 L
Front axle	3.5 L



Hoekstraat 179, 9160 Eksaarde - Lokeren. België

+32 (9) 355 56 29

info@garagecnudd.be www.garagecnudd.be

bezoek onze nieuwe website **www.tymtractors.be**

PTO		
PTO type	Transmission PTO w/ ORC/ Independent	
PTO control	Electric/Hydro	
PTO rear	540 rpm	
HYDRAULIC SYSTEM		
Pump type	Single gear pump	
Implement flow	15.8 L/min	
Steering flow	10.5 L/min	
Total flow	26.3 L/min	
Category, 3-point hitch	I (N)	
Hitch lift capacity	750 kg	
Frontloader lift capacity	800 kg	
Lift control type	Position	
No. of standard remote valves	1	
DIMENSIONS & WEIGHTS		
Overall length with 3-point hitch	2668 mm	
Overall width	1286 mm	
Wheelbase	1460 mm	
Height to top of ROPS	2320 mm	
Height to top of cabin	2350 mm	
Min. ground clearance	240 mm	
Min. turn radius with brakes	2250 mm	
Min. turn radius without brakes	2540 mm	
Weight with ROPS	843 kg	
Maximum weight with trailer	3550kg	
STANDARD TIRES		
Agricultural - Front / Rear	6.0-12 4PR / 9.5-16 6PR	1180 mm
Industrial - Front / Rear	20x8.0-10 4PR / 27x12.5-15 4PR	1250 mm
Galaxy pro (optional) - Front / Rear	200/60 R15 / 280/70 R18	1200 mm